

HT

series
Wire Twister



Easy



Speed



UI




Touch LCD

- Accurate control of fixed position and rotation speed is possible by using servomotor
- Automatic drop after twist(No need to press clamp release button) - UPH raising effect
- Ability to scan work instructions and MES & ERP



► Media for this

HT Wire Twister



Technical Data

ITEM	HT-04N	HT-06N	HT-08N	HT-10N
OPERATING SYSTEM	Microsoft Windows 10			
OPERATING LANGUAGE	Korean, English, Chinese, Spanish, etc.			
POWER	A.C 100~240V 50/60Hz Built in UPS			
WORKING PRESSURE	0.5~0.6 MPa			
WEIGHT	490 kg	566 kg	642 kg	718 kg
SIZE(WxDxH, mm)	5300x560x1555	7300x560x1555	9300x560x1555	11300x560x1555
WORKING RANGE	100~4000 mm	100~6000 mm	100~8000 mm	100~10000 mm
WIRE THICKNESS	0.13~2.0 SQ			
WIRE TYPE	AVSS, AVSSX, AVSSXF, CHFUS			
UNWINDING LENGTH	30~80 mm			
ROTATE SPEED	0~1500 RPM			
DISPLAY	24" FHD Touch Display			
COMMUNICATION PORT	LAN			
etc.	Built in OS Recovery System			

Options



- Barcode Scanner



- UI Customizing

- System Customizing
- MES Connection Available
- LOG System(DB)

Headquarters

#1313, 184, Gasan digital 2-ro, Geumcheon-gu, Seoul 08501, Republic of Korea

Hwaseong Branch

1085-33, Beodeul-ro, Jangan-myeon, Hwaseong-si, Gyeonggi-do 18574, Republic of Korea

China Branch

No. 6-3, Changxing-Road, Economic & Technological Development zone, Weihai, Shandong, China(山东省威海经济技术开发区昌星路6-3号)

Vietnam Bac Ninh Branch

Yen phong zone, Long Chau commune, Yen Phong distric, Bac Ninh province, Vietnam

