









- A leak tester that detects missing waterproof seals and can support up to 200 connectors using air
- With a simple user interface, the workers to be able to confirm the missing of the waterproof seal more quickly
- Using a unique inspection process, we can quickly detect if the waterproof seal is missing



Media for this

LT Leak Tester




•	



Technical Data

ITEM	LT	REMARK
OPERATING SYSTEM	RTOS	
LANGUAGE	English	
POWER	A.C 100~240V 50/60Hz	
WEIGHT	Max. 18 kg	Standard : LT40
SIZE	450(W)x350(D)x210(H) mm	
СН	10CH, 20CH, 30CH, 40CH	Expand Max. 200CH
TEST TYPE	Pressure, Vacuum	
TEST RANGE	Pressure : 0.1~1.5 bar / Vacuum : 0.1~0.8 bar	
ACCURACY	0.02 bar	
OPERATING PRESSURE	0.5~0.6 MPa	
DISPLAY	10.2" TFT Color LCD	
COMMUNICATION PORT	RS232C, Start(Input) Signal, Pass(Output) Signal	
etc.	Operation NG Guide Manual Testing Manual Operation Set to CH Value & Time	

Options





• Auto Start System

• Washer Hose Test System



Headquarters

#1313, 184, Gasan digital 2-ro, Geumcheon-gu, Seoul 08501, Republic of Korea

Hwaseong Branch

1085-33, Beodeul-ro, Jangan-myeon, Hwaseong-si, Gyeonggi-do 18574, Republic of Korea

China Branch

No. 6-3, Changxing-Road, Economic & Technological Development zone, Weihai, Shandong, China(山东省威海经济技术开发区昌星路6-3号)

Vietnam Bac Ninh Branch

Yen phong zone, Long Chau commune, Yen Phong distríc, Bac Ninh province, Vietnam

