

SWC

series
Shield Wire Cutter



Inspection



Safety



Easy



Speed







UI

- Various SQ high voltage shield wire can be cut off simply by replacing the pipe jig
- Cutting length can be set without changing parts separately
- PC-based MES integration



► Media for this

SWC Shield Wire Cutter



Technical Data

ITEM	SWC100
OPERATING SYSTEM	Microsoft Windows 10
OPERATING LANGUAGE	Korean, English, Chinese, Japanese, Spanish, etc.
SIZE	540(W)X1200(D)X1590(H) mm(Include Monitor) 490(W)X1200(D)X1205(H) mm(Exclude Monitor)
WEIGHT	250 kg
POWER	A.C 100~240V 50/60Hz, Built in UPS
JACKET TO SHIELD DISTANCE	3~50 mm
DISPLAY	24" FHD Touch Display
WORKING RANGE	5~200 mm
WIRE THICKNESS	Ø4.5~13 (External diameter of the inner sheath)
WIRE TYPE	AHHEX-BS, FHL2XC2X
ROTATION COUNT	4 (0.5RPM)
WORKING PRESSURE	0.3~0.35 MPa
etc.	Built in OS Recovery System

Options



- Barcode Scanner

- UI Customizing

- MES Connection Available

- LOG System(DB)

HARNICS

FROM TECH TO INNOVATION

Headquarters

#1313, 184, Gasan digital 2-ro, Geumcheon-gu, Seoul 08501, Republic of Korea

China Branch

No. 6-3, Changxing-Road, Economic & Technological Development zone, Weihai, Shandong, China
(山东省威海经济技术开发区昌星路6-3号)

Vietnam Bac Ninh Branch

Yen phong zone, Long Chau commune, Yen Phong distríc, Bac Ninh province, Vietnam

