

# HT

series  
**Wire Twister**



Easy



Speed



UI




Touch LCD

- Accurate control of fixed position and rotation speed is possible by using servomotor
- Automatic drop after twist(No need to press clamp release button) - UPH raising effect
- Ability to scan work instructions and MES & ERP



► Media for this

# HT Wire Twister



## Technical Data

ITEM	HT-04N	HT-06N	HT-08N	HT-10N
OPERATING SYSTEM	Microsoft Windows 10			
OPERATING LANGUAGE	Korean, English, Chinese, Spanish, etc.			
POWER	A.C 100~240V 50/60Hz Built in UPS			
WORKING PRESSURE	0.5~0.6 MPa			
WEIGHT	490 kg	566 kg	642 kg	718 kg
SIZE(WxDxH, mm)	5300x560x1555	7300x560x1555	9300x560x1555	11300x560x1555
WORKING RANGE	100~4000 mm	100~6000 mm	100~8000 mm	100~10000 mm
WIRE THICKNESS	0.13~2.0 SQ			
WIRE TYPE	AVSS, AVSSX, AVSSXF, CHFUS			
UNWINDING LENGTH	30~80 mm			
ROTATE SPEED	0~1500 RPM			
DISPLAY	24" FHD Touch Display			
COMMUNICATION PORT	LAN			
etc.	Built in OS Recovery System			

## Options



- Barcode Scanner



- UI Customizing

- System Customizing
- MES Connection Available
- LOG System(DB)

**HARNICS**  
FROM TECH TO INNOVATION

### Headquarters

#1313, 184, Gasan digital 2-ro, Geumcheon-gu, Seoul 08501, Republic of Korea

### China Branch

No. 1-2, Tianning Road, Caomiaozi Town, Lingang Economic and Technological Development Zone, Weihai, Shandong 264211, China  
(山东省威海临港经济技术开发区草庙子镇天宁路1-2号)

### Vietnam Branch

Lot CN7-3, Yen Phong II-C Industrial Park, Cho Town, Yen Phong District, Bac Ninh Province 16206, Vietnam



www.harnics.com