















esv Sn

Speed

Ш

Touch LCD

- Equipment that allows one worker to twist two sets of wires continuously using two heads
- Twisting wires of various lengths and thicknesses
- Continuous operation(crossing) The two axes allow loading on one side and twist on the other



WT Wire Twister









Technical Data

ITEM	WT-02M	WT-04M	WT-06M	WT-08M	WT-10M
OPERATING SYSTEM	Microsoft Windows 10				
OPERATING LANGUAGE	Korean, English, Chinese, Spanish, etc.				
POWER	A.C 100~240V 50/60Hz Built in UPS				
OPERATING PRESSURE	0.5~0.6 MPa				
WEIGHT	414 kg	490 kg	566 kg	642 kg	718 kg
SIZE(W x D x H, mm)	3600x1850x900	5600x1850x900	7600x1850x900	9600x1850x900	11600x1850x900
WORKING RANGE	220~2000 mm	220~4000 mm	220~6000 mm	220~8000 mm	220~10000 mm
WIRE THICKNESS	0.22~2.0 SQ				
WIRE TYPE	AVSS, AVSSXF, CHFUS, etc.				
DISPLAY	24" FHD Touch Display				
MOVING SPEED	2500 mm/sec				
ROTATE SPEED	750 RPM				
COMMUNICATION PORT	USB				
etc.	Barcode Scanner, Built in OS Recovery System				

Options



• Barcode Scanner

FROM TECH TO INNOVATION

• LOG System(DB)

- MES Connection Available
- SystemCustomizing
- UI Customizing



Headquarters

#1313, 184, Gasan digital 2-ro, Geumcheon-gu, Seoul 08501, Republic of Korea

China Branch

No. 1-2, Tianning Road, Caomiaozi Town, Lingang Economic and Technological Development Zone, Weihai, Shandong 264211, China (山东省威海临港经济技术开发区草庙子镇天宁路1-2号)



Vietnam Branch Lot CN7-3, Yen Phong II-C Industrial Park, Cho Town, Yen Phong District, Bac Ninh Province 16206, Vietnam

